

MiTek® *Peak-Up Stacker*

Truss Stacker and Optional Powered Conveyor



Saves on labor...

MiTek®
MiTek®



MiTek® Peak-Up Stacker

Truss Stacker and Optional Powered Conveyor



Heavy-duty drive system



Receiver stand with automatic indexing



Optional Pop-up target

Specifications

- Saves labor and helps reduce costly injuries
- Improves use of valuable in-plant space when positioned outdoors
- Easily stacks any truss 16'-0" to 60'-0" in length and 14'-0" in height, and will accommodate up to 80'-0" lengths
Requires Dual Peak-Up Stackers
- Standard capacity is 30 trusses
- Adjustable bridge starts stacking cycle
- Average stacking cycle time is 40 seconds
- Bundle indexes back 1-1/2" as each truss is stacked
- Electric/mechanical controls and drive system operate in all weather conditions
- Available in 1200 lb. capacity

**INTEGRATING
MANUFACTURING
with DESIGN**

Powered Conveyor Data

- 1/2 horse-power drive motor on each powered conveyor section
- 4-1/2" diameter rollers 60" on center
- Every other roller is powered
- Guarding provided for "V"-belt drive system
- Stand alone conveyor allows walk through aisles between each roller



MiTek Industries, Inc. 800.325.8075 Fax 314.434.5343 www.mii.com
14515 North Outer Forty • Chesterfield, MO 63017